



CPR Declaration of Performance (DoP)

DoP reference:

NAAC001 UKCA DOP

1. Unique identification code of the product type (in combination with point 2):

BS EN 13108-1:2016 Bituminous mixtures - Material specifications Part 1: Asphalt Concrete

2. Identification of the construction product:

Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC10 Close Surface 100/150

3. Intended use:

BS EN 13108-1:2016 Bituminous mixtures
For use on roads, airfields and other trafficked areas

4. Company name:

Newlay Asphalt Limited
Elite House
Spellowgate
Driffield
East Yorkshire
YO25 5UP

5. Authorised representative:

Jamie Brown (address as above)

6. System of assessment:

Attestation Level 2+

7. Standard and UK Approved body:

Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR – 623633; a UKAS accredited certification body and a UK approved body under Article 9 of the Construction Products Regulation (EU) No 305/2011 as amended by The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465).

8. European Technical Assessment (ETA):

Not applicable

continued...

9. Declared performance:

Essential Characteristics	Declared values		
	Sieve Size (mm)	Passing (%)	Tolerance
Target Composition (Grading)	14.000	100.00	As EN 13108-1
	10.000	98.00	As EN 13108-1
	6.300	68.00	As EN 13108-1
	2.000	29.00	As EN 13108-1
	1.000	21.00	As EN 13108-1
	0.063	5.00	As EN 13108-1
Binder Content	5.20%		
Temperature Range	120 to 170 Degees C.		
Void Content (Maximum)	V _{max} NR		
Void Content (Minimum)	V _{min} NR		
Water Sensitivity	ITSR NR		
Resistance to Abrasion	ABR NR		
Reaction to Fire	Euroclass CfI NR		
Stiffness (Maximum)	S _{max} NR		
Stiffness (Minimum)	S _{min} NR		
Resistance to Permanent Deformation	F _{cmax} NR		
Coarse Aggregate	BS EN 12620 - As Approved Supplier List		
Fine Aggregate	BS EN 12620 - As Approved Supplier List		
Filler Aggregate	BS EN 12620 (Natural or Extracted) - As Approved Supplier List		
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.		CPR DoP Electronic Provision No. 305/2011


10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Jamie Brown (Director), issued at the address given in point 4, 01 Jan 2024.

Signature: *Jamie Brown*

Supporting information:

The UKCA Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement, invoice or direct email at the client's request (i.e. delivered either in hard-copy or electronic format within an email).

2024  0086	BS EN 13108-1:2016 UKCA Mark ref. NAAC001 Dated 01 Jan 2024 Bituminous mixtures - Material specifications Part 1: Asphalt Concrete Newlay Asphalt Limited Elite House, Spellowgate, Driffield, East Yorkshire, YO25 5UP																					
Source and material description: Newlay Asphalt Dewsbury Plant - Asphalt Concrete - AC10 Close Surface 100/150																						
Intended use: For use on roads, airfields and other trafficked areas																						
Attestation Level 2+ Certified by UK Approved Body BSI - Ref. 0086 - CPR - 623633																						
Essential Characteristics	Declared values																					
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Sieve Size (mm)</th> <th style="width: 30%;">Passing (%)</th> <th style="width: 40%;">Tolerance</th> </tr> </thead> <tbody> <tr> <td>14.000</td> <td>100.00</td> <td>As EN 13108-1</td> </tr> <tr> <td>10.000</td> <td>98.00</td> <td>As EN 13108-1</td> </tr> <tr> <td>6.300</td> <td>68.00</td> <td>As EN 13108-1</td> </tr> <tr> <td>2.000</td> <td>29.00</td> <td>As EN 13108-1</td> </tr> <tr> <td>1.000</td> <td>21.00</td> <td>As EN 13108-1</td> </tr> <tr> <td>0.063</td> <td>5.00</td> <td>As EN 13108-1</td> </tr> </tbody> </table>	Sieve Size (mm)	Passing (%)	Tolerance	14.000	100.00	As EN 13108-1	10.000	98.00	As EN 13108-1	6.300	68.00	As EN 13108-1	2.000	29.00	As EN 13108-1	1.000	21.00	As EN 13108-1	0.063	5.00	As EN 13108-1
Sieve Size (mm)	Passing (%)	Tolerance																				
14.000	100.00	As EN 13108-1																				
10.000	98.00	As EN 13108-1																				
6.300	68.00	As EN 13108-1																				
2.000	29.00	As EN 13108-1																				
1.000	21.00	As EN 13108-1																				
0.063	5.00	As EN 13108-1																				
Binder Content	5.20%																					
Temperature Range	120 to 170 Degees C.																					
Void Content (Maximum)	V _{max} NR																					
Void Content (Minimum)	V _{min} NR																					
Water Sensitivity	ITSR NR																					
Resistance to Abrasion	ABR NR																					
Reaction to Fire	Euroclass CfI NR																					
Stiffness (Maximum)	S _{max} NR																					
Stiffness (Minimum)	S _{min} NR																					
Resistance to Permanent Deformation	F _{cmax} NR																					
Coarse Aggregate	BS EN 13043 - As Approved Supplier List																					
Fine Aggregate	BS EN 13043 - As Approved Supplier List																					
Filler Aggregate	BS EN 13043 (Natural or Extracted) - As Approved Supplier List																					
Declaration of Performance	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;"> <small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.</small> </td> <td style="width: 30%; text-align: center;"> CPR DoP Electronic Provision No. 305/2011 </td> </tr> </table>	<small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.</small>	CPR DoP Electronic Provision No. 305/2011																			
<small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site https://www.newlayasphalt.co.uk/certification (or will be supplied directly). The appropriate DoP is referenced NAAC002 UKCA DOP on the UKCA Regulations page and/or on formal documentation.</small>	CPR DoP Electronic Provision No. 305/2011																					

Please contact us should you require any further information.